

ATESS ESS-BM-51.2-280R

ATESS ESS-BM-51.2-280RAB-A

ATESS ESS-BM-51.2-280RAB-B

ATESS ESS-BM-51.2-280RAB-A-1C

ATESS ESS-BM-51.2-280RAB-B-1C



LEADING - EDGE TECHNOLOGY

Datasheet

Battery module specification

	ATESS ESS-BM-51.2-280RAB-A ATESS ESS-BM-51.2-280RAB-B	ATESS ESS-BM-51.2-280RAB-A-1C ATESS ESS-BM-51.2-280RAB-B-1C
Cell Configuration	16S1P	16S1P
Rated capacity	280Ah	280Ah
Rated voltage	51.2V	51.2V
Rated energy	14.336kWh	14.336kWh
Voltage range	44.8~57.6V	44.8~57.6V
Rated charge/discharge	0.5C	1C
AC internal resistance	≤8mΩ	≤8mΩ
Dimension(W/H/D)	523/231/805mm	523/231/805mm
Weight	113kg	113kg
Cell balancing	Active balancing	Active balancing

Shenzhen Ateess Power Technology Co.,Ltd

GROWATT-ATESS Industrial Park, No.23 Zhulongtian Road, Shuitian Community, Shiyan Street, Baoan District, Shenzhen