


# Accessories



Model	NOVO EVA-07/11/22S-S/P	NOVO EVA-07/09/12S-PU	NOVO EVA-07/11/22D-SEW/PEW
Mounting pole			
Dimension (W/H/D)	255/1500/154mm	255/1500/154mm	360/906.5/250mm
Weight	11kg	11kg	10kg



Model	EVD-20S	EVD-40SU/DU	EVD-80D
Mounting pole			
Dimension (W/H/D)	360/1500/260mm	500/1652/300mm	500/1652/300mm
Weight	14kg	31kg	31kg



Model	EVD-40S	EVD-40D
Mounting pole		
Dimension (W/H/D)		500/1652/300mm
Weight		30kg



Model	CARD WRITER
Contactless IC card	Supports Mifare 1 cards, TypeA CPU cards, and TypeB CPU cards that comply with the ISO14443 standard widely applied in the market.
Standard	RF interface that complies with ISO/IEC14443 TypeA and TypeB standard
Working frequency	13.56 MHz
Perating temperature	-20°C ~ 65°C;
Storage temperature	-20°C ~ 70°C;
Relative humidity	20-90%
Protection	TypeA CPU cards and TypeB CPU cards (embedded with CPU chips) for better encryption and security



Model	Multi-charge manager		
Specification			
System capacity	50KW	100KW	240KW
Normal input voltage/ range	400Vac 320~480Vac		
Normal input frequency/ range	50/60Hz 45-55Hz/55-65Hz		
Max. detection current	150A	250A	600A
Charger max. connection number	32PCS		
Max. communication distance	RS485 shielded twisted pair cable : 500m Ethernet cable : 100m		
Dimensions(W/H/D)	400*362*160mm		
Weight	10KG		
Operating temperature	-20°C~+50°C		
Protection degree	IP 65		
Relative humidity	0~95%		
Certification	CE		