


NOVO EVA-07/11/22S-S

NOVO EVA-07/11/22S-P

AC EV charging station for home or light commercial use, plug or socket type optional, single output.



Features

-  Programmable charging mode
-  Comprehensive protection
-  Multiple communication modes
-  Compact and exquisite
-  EU standard
-  Flexible installation

Model	NOVO EVA-07S-S/P	NOVO EVA-11S-S/P	NOVO EVA-22S-S/P
Input & Output			
Input voltage	230V AC	400V AC	400V AC
Input frequency		50Hz/60Hz	
Output voltage	230V AC	400V AC	400V AC
Max.output power	7.3kW	11kW	22kW
Max.output current	32A	16A	32A
Charging interface type		IEC62196-2,Type2	
Connection		Socket/ Plug (opt)	
Cable Length		5m	
Protection			
Over voltage protection		Yes	
Under voltage protection		Yes	
Over load protection		Yes	
Residual current detection		AC 30mA + DC 6mA	
Over-temp protection		Yes	
Lightning protection		Yes	
Function & Accessory			
Ethernet/WIFI/4G		Yes/Yes/Opt	
LCD		Opt	
Charging Mode		APP/RFID(Opt)/Plug and charge	
LED Indicator Light		Yes	
Intelligent power adjustment		Yes	
PV linkage		Yes	
Installation		Floor/wall-mounting	
MID meter		Opt	
Appearance colour		Black/Silver	
OCP		1.6JSON	
Working Environment			
Ingress Protection		IP65	
Operating temperature		-25°C ~+50°C	
Relative humidity		5-95% non-condensing	
Maximum altitude		2000m	
Cooling		Natural air cooling	
Standby power consumption		<8W	
Mechanical			
Dimension (W/H/D)		246/382/162mm	
Weight	< 3kg(without plug)	< 3.5kg(without plug)	< 3.5kg(without plug)
	<5kg (with plug)	<5.5kg (with plug)	<6.5kg (with plug)
Certificate			
		CE RCM CB	