



Product Service

Attestation of Conformity

No. N8A 110886 0006 Rev. 00

Holder of Certificate: **Shenzhen Ates Power Technology Co.,Ltd**
1st Floor of Building 3 at Sector B and
3rd Floor of Building 9,Henglong Industrial Park, Shuitian
Baoan District
518724 Shenzhen
PEOPLE'S REPUBLIC OF CHINA

Product: **AC electric vehicle charging station
(Electric Vehicle Supply Equipment)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64105223001401

Date, 2022-09-16


(Glenn Liu)

Page 1 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 110886 0006 Rev. 00

Model(s):

NOVO EVA series
NOVO EVA-XXD-XX W
 I II III IV

I: "NOVO EVA" denotes for basic model designation, "NOVO EVA" can be:

NOVO EVA: NOVO EVA series

II: "XXD" denotes for power, "XXD" can be:

07D: 7kW+7kW

11D: 11kW+11kW

22D: 22kW+22kW

III: "XX" denotes for vehicle connection method, "XX" can be:

PE: vehicle connector with 5m cable

SE: type 2 socket-outlet

IV: "W" denotes for mounting means, "W" can be:

Blank: Ground mounted

W: Wall mounted

Brand:

ATESS



Parameters:

Rated input Voltage (V):	For NOVO EVA-07D series: 1P+N+PE, 230Vac, 50Hz; For NOVO EVA-11D series: 3P+N+PE, 400Vac, 50Hz; For NOVO EVA-22D series: 3P+N+PE, 400Vac, 50Hz.
Rated input current(A):	For NOVO EVA-07D series: 32A+32A; For NOVO EVA-11D series: 16A+16A; For NOVO EVA-22D series: 32A+32A.
Output voltage (V):	Same as input voltage.
Output current (A):	Same as input current.
Output power(kW):	For NOVO EVA-07D series: 7kW+7kW; For NOVO EVA-11D series: 11kW+11kW; For NOVO EVA-22D series: 22kW+22kW.
Protection class:	Class I
Degree of protection:	For NOVO EVA-XXD-SEW models: IP55; For NOVO EVA-XXD-PEW models: IP65. (Vehicle connector IP54)
Working temperature (°C):	-25 ~ +50°C

Page 2 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 110886 0006 Rev. 00

**Tested
according to:**

EN IEC 61851-1:2019

Page 3 of 3

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.