

# NOVO EVA-07/11/22D-SE

# NOVO EVA-07/11/22D-PE

Floor-standing type AC EV charging station, plug or socket type optional, dual output.



## Features



Programmable charging mode



Dual output ports



Comprehensive protection



EU standard



Multiple communication modes



Floor-standing design

Model	NOVO EVA-07D-SE/PE	NOVO EVA-11D-SE/PE	NOVO EVA-22D-SE/PE
<b>Input &amp; Output</b>			
Input voltage	230V AC	400V AC	400V AC
Input frequency		50Hz/60Hz	
Output voltage	230V AC	400V AC	400V AC
Max.output power	7.3kW*2	11kW*2	22kW*2
Max.output current	32A*2	16A*2	32A*2
Charging interface type		IEC62196-2,Type2	
Connection		Socket/ Plug (opt)	
Cable Length		5m	
Number of connection		2	
<b>Protection</b>			
Over voltage protection		Yes	
Under voltage protection		Yes	
Over load protection		Yes	
Short circuit protection		Yes	
Earth leakage protection		TypeA+6mA DC Fault current protection	
Over-temp protection		Yes	
Lightning protection		Yes	
<b>Function &amp; Accessory</b>			
Ethernet/WIFI/4G		Yes/Yes/Opt	
LCD		Opt	
Charging Mode		APP/RFID(Opt)/Plug and charge	
LED Indicator Light		Yes	
Intelligent power adjustment		Yes	
PV linkage		Yes	
Installation		Floor	
Pro-earth		Opt	
MID meter		Opt	
OCP		1.6JSON	
<b>Working Environment</b>			
Ingress Protection		IP55/ IP65	
Operating temperature		-25°C ~+50°C	
Relative humidity		5-95% non-condensing	
Maximum altitude		2000m	
Cooling		Natural air cooling	
Standby power consumption		<8W	
<b>Mechanical</b>			
Dimension (W/H/D)		420/1639/270mm	
Weight	< 19kg(without plug)	< 22kg(without plug)	< 22kg(without plug)
	< 23kg(with plug)	< 26kg(with plug)	< 28kg(with plug)
<b>Certificate</b>			
		CE RCM	