

NOVO EVA-07/11/22S-SE

NOVO EVA-07/11/22S-PE

AC EV charging station for home use or light commercial use, plug or socket type optional, single output.



Features



Programmable charging mode



Compact and exquisite



Comprehensive protection



EU standard



Multiple communication modes



Flexible installation

Model	NOVO EVA-07S-SE/PE	NOVO EVA-11S-SE/PE	NOVO EVA-22S-SE/PE
Input & Output			
Input voltage	230V AC	400V AC	400V AC
Input frequency		50Hz/60Hz	
Output voltage	230V AC	400V AC	400V AC
Max.output power	7kW	11kW	22kW
Max.output current	32A	16A	32A
Charging interface type		IEC62196-2,Type2	
Connection		Socket/ Plug (opt)	
Cable Length		5m	
Protection			
Over voltage protection		Yes	
Under voltage protection		Yes	
Over load protection		Yes	
Residual current detection		AC 30mA + DC 6mA	
Over-temp protection		Yes	
Lightning protection		Yes	
Function & Accessory			
Ethernet/WIFI/4G		Yes/Yes/Opt	
LCD		Opt	
Charging Mode		APP/RFID(Opt)/Plug and charge	
LED Indicator Light		Yes	
Intelligent power adjustment		Yes	
PV linkage		Yes	
Installation		Floor/wall-mounting	
Pro-earth		Yes	
MID meter		Opt	
Appearance colour		Black/Silver	
OCPP		1.6JSON	
Working Environment			
Ingress Protection		IP65	
Operating temperature		-25°C ~+50°C	
Relative humidity		5-95% non-condensing	
Maximum altitude		2000m	
Cooling		Natural air cooling	
Standby power consumption		<8W	
Mechanical			
Dimension (W/H/D)		246/382/162mm	
Weight	< 3kg(without plug)	< 3.5kg(without plug)	< 3.5kg(without plug)
	<5kg (with plug)	<5.5kg (with plug)	<6.5kg (with plug)
Certificate			
		CE RCM	